

Wireless N PCI Adapter TL-WN951N



300Mbps wireless transmission rate with 3 antennas, brings smooth wireless N experience

MIMO, CCA™ technology, brings competitive performance in 11n routers

QSS, Quick Secure Setup, complies with WPS for effortless wireless security setup




Description:

The TL-WN951N Wireless N PCI Adapter complies with IEEE 802.11n, IEEE 802.11g, and IEEE 802.11b standards. Wireless transmission rates can reach up to 300Mbps. The PCI Card with three external detachable Omni-directional antennas works well with other 11g and 11n protocol wireless products and adopts MIMO as well as SST™ technology which can bring a faster, wider, and more stable wireless experience. This product can also simultaneously operate bandwidth intensive applications using a lot of bandwidth which are sensitive to interruption. When using multiple bandwidth intensive applications, the most sensitive of these applications can be given priority over the others to be allocated more bandwidth in order to assure quality.

Specifications:

Standards	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b, CSMA/CA with ACK
Interface	32-bit PCI 11n: 270/243/216/162/108/81/54/27Mbps 135/121.5/108/81/54/40.5/27/13.5Mbps
Wireless Signal Rates With Automatic Fallback	130/117/104/78/52/39/26/13Mbps 65/58.5/52/39/26/19.5/13/6.5Mbps 11g: 54/48/36/24/18/12/9/6M (adaptive) 11b: 11/5.5/2/1M (adaptive)
Frequency Range	2.4-2.4835GHz
Wireless Transmit Power	20dBm(MAX)
Modulation Type	OFDM/CCK/16-QAM/64-QAM 270M: -68dBm@10% PER 130M: -68dBm@10% PER 108M: -68dBm@10% PER 54M: -68dBm@10% PER 11M: -85dBm@8% PER 6M: -88dBm@10% PER 1M: -90dBm@8% PER
Receiver Sensitivity	
Antenna	2dBi detachable Omni directional antenna x 3
Security	64/128/152 bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK (TKIP/AES)
Certifications	CE, FCC
Support Operating System	Windows 7/Vista/XP/2000
Operating temperature	0°C~40°C (32°F~104°F)
Storage temperature	-40°C~70°C (-40°F~158°F)
Relative humidity	10% ~ 90%, non condensation
Storage Humidity	5%~95% non-condensing
Dimensions	133 × 121 × 22 (mm) 5.2 × 4.8 × 0.9 (in.)

Diagram:



Features:

- Provides 32-bit PCI connector
- Provides Infrastructure and Ad-Hoc modes
- 300M wireless transmission rate, adopts MIMO, SST™, CCA™ technology, allows for faster speed, further wireless coverage, more stable performance
- Quick Secure Setup, complies with WPS for worry free wireless security
- Supports 64/128/152 strength WEP encryptions, as well as WPA/WPA2 and WPA-PSK/WPA2-PSK encryptions and mechanisms
- Web-site Configuration and monitoring
- Supports Roaming technology, guarantees efficient wireless connections.
- Supports Windows 7/Vista/XP/2000

Package:

- Wireless N PCI Adapter TL-WN951N with 3 detachable antennas
- Quick Setup Guide
- Resource CD, including:
 - TL-WN951N Wireless Client Utility and Drivers
 - User Guide
 - Other Helpful Information

Related Products:

- Wireless N Router TL-WR941ND
- Wireless N Cardbus Adapter TL-WN910N
- 54M Wireless ADSL2+ Router TD-W8920G

Specifications are subject to change without notice. TP-LINK is a registered trademark of TP-LINK Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. No part of the specifications may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from TP-LINK Technologies Co., Ltd.